

Safety Data Sheet

according to OSHA Hazard Communication
29 CFR Part 1910.1200



SECTION 1. Identification

Product Name: DuraMAX Brake Cleaner
SDS #: 950769999BC

Supplied by: RelaDyne, LLC.
9395 Kenwood Rd, Suite 104
Blue Ash, OH 45242
888-830-3156
www.reladyne.com

24 Hour Emergency:

INFOTRAC: 1-800-535-5053

NOTE: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

SECTION 2. Hazard(s) Identification

***** EMERGENCY OVERVIEW ***:** Extremely flammable liquid and vapor. May be fatal if inhaled. May be fatal if swallowed. Suspect cancer hazard.

GHS Classification

Carc. 2, Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 NE, Skin Irrit. 2

Symbol(s) of Product



Signal Word

Danger

GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapor.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.

GHS PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor/physician if you feel unwell.
P321	Specific treatment (see first aid section on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
2-propanone	67-64-1	50-75	GHS02-GHS07	H225-319-336
Naphtha (petroleum), hydrotreated light	64742-49-0	25-50	GHS02-GHS07	H225-315-336
Xylene	1330-20-7	2.5-10	GHS02-GHS07- GHS08	H226-315-319-332-335-351-373
Ethylbenzene	100-41-4	1.0-2.5	GHS02-GHS07- GHS08	H225-315-319-332-335-351-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

SECTION 4. First-Aid Measures



FIRST AID - EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly. Remove contact lenses if worn.

FIRST AID - SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately and clean shoes before reuse.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID - INGESTION: Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

SECTION 5. Fire-Fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extremely flammable liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Closed container may explode under extreme heat.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Evacuate all unnecessary personnel. Shut down motors, pumps, electrical service and eliminate all sources of ignition. Avoid use of solid water streams. Do not use water jet (frothing possible). Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Small fire: dry chemicals, carbon dioxide, foam, water fog, or inert gas (nitrogen); Large fire: Foam, water fog, or water spray.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Evacuate unnecessary personnel. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. If leak or spill has not ignited, use water spray to disperse the vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 7. Handling and Storage



HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-resistant tools. Do not load into compartments adjacent to heated cargo. Use explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all SDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

SECTION 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH-TLV-TWA</u>	<u>ACGIH-TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
2-propanone	500 ppm	750 ppm	1000 ppm	N.D.
Naphtha (petroleum), hydrotreated light	400 ppm	500 ppm	500 ppm	N.D.
Xylene	100 ppm	150 ppm	100 ppm	N.D.
Ethylbenzene	100ppm	125ppm	100ppm	N.D.

Personal Protection



RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.



SKIN PROTECTION: Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.



EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.



OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



HYGIENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

SECTION 9. Physical and Chemical Properties

Appearance:	N.D.	Physical State:	Liquid
Odor:	Typical	Odor Threshold:	N.D.
Density, g/cm³:	0.767	pH:	N.D.
Freeze Point, °F:	N.D.	Viscosity:	N.D.
Solubility in Water:	N.D.	Explosive Limits, vol%:	1.0 - 12.8
Boiling Range, °F:	133 - 288	Flash Point, °F:	0
Evaporation Rate:	N.D.	Auto-ignition Temp., °F:	N.D.
Vapor Density:	N.D.	Vapor Pressure:	N.D.

(See "Other information" Section for abbreviation legend)

SECTION 10. Stability and Reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBILITY: Keep separate from alkalis. Prevent contact with halogens. Prevent contact with strong oxidizing agents. Keep away from acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed. During combustion asphyxiants may be formed.

HAZARDOUS POLYMERIZATION: No Information

SECTION 11. Toxicological Information



Information on Toxicological Effects

EFFECTS OF OVEREXPOSURE - INHALATION: May be fatal if inhaled. Breathing in the material may irritate the mucous membranes of the nose, throat bronchi and lungs. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). May cause dizziness and drowsiness. High vapor concentrations may cause drowsiness.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Contact with skin may cause mild irritation. Causes skin irritation. Can be absorbed through skin and produce central nervous system effects. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation. Contact with the eye may cause mild irritation. Symptoms may include stinging, tearing, redness and swelling.

EFFECTS OF OVEREXPOSURE - INGESTION: May be fatal if swallowed. Harmful or fatal if liquid is aspirated into lungs. Irritating to mouth, throat, and stomach. Ingestion may cause gastrointestinal tract irritation. Can be readily absorbed by the stomach and intestinal tract. Symptoms include burning sensation of the mouth and esophagus, nausea, vomiting, diarrhea, dizziness, staggering gait, drowsiness, loss of consciousness and delirium as well as additional central nervous system effects. May cause nausea and diarrhea. Ingestion may result in nausea, vomiting, diarrhea and restlessness. May cause dizziness and drowsiness and/or stupor.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Suspect cancer hazard. Possible brain damage from overexposure. The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Overexposure may cause nervous system damage. May cause delayed lung damage. Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50, mg/L</u>
67-64-1	2-propanone	5800.0	20000.0	76.0
64742-49-0	Naphtha (petroleum), hydrotreated light	>5000	>5000	>20.0
1330-20-7	Xylene	>3523	>4200	>20.0
100-41-4	Ethylbenzene	3500	15433	>20.0

SECTION 12. Ecological Information

ECOLOGICAL INFORMATION: No Information

SECTION 13. Disposal Considerations

For more guidance and information contact our Waste Services Division at (262) 658-4000.

Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: Dispose of waste in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.) Eliminate all ignition sources. Evacuate unnecessary personnel. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. If leak or spill has not ignited, use water spray to disperse the vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

SECTION 14. Transport Information

DOT Proper Shipping Name:	Flammable liquids, n.o.s. (acetone, heptane)	Packing Group:	II
DOT Hazard Class:	3	Hazard SubClass:	No Information
DOT UN/NA Number:	UN1993	Resp. Guide Page:	0

SECTION 15. Regulatory Information**U.S. Federal Regulations:****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Xylene	1330-20-7
Ethylbenzene	100-41-4
Toluene	108-88-3
Benzene	71-43-2

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations:**NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethylbenzene	100-41-4
Benzene	71-43-2

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
Toluene	108-88-3
Benzene	71-43-2

International Regulations: As follows -**CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

SECTION 16. Other Information

Revision Date: 6/29/2015 Supersedes Date: New SDS

Datasheet produced by: EH&S - Regulatory Department

HMIS Ratings:

Health:	1	Flammability:	3	Reactivity:	0 - No Hazard	Personal Protection:	X
---------	---	---------------	---	-------------	---------------	----------------------	---

Volatile Organic Compounds, gr/ltr: 78

DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, EMCO MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/ REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

- GHS02 
- GHS07 
- GHS08 

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.