

SAFETY DATA SHEET

1. Identification

RelaTECH Premium Soluble 2550B **Product identifier**

METALWORKING FLUID

Other means of identification

9516225BSO SDS number

METALWORKING FLUID Recommended use

Recommended restrictions None known

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name RelaDyne, LLC

9395 Kenwood Rd, Suite 104

Blue Ash, OH 45242

Telephone (General

Information)

888-830-3156 www.reladvne.com

Emergency telephone

number

INFOTRAC 800-535-5053

2. Hazard(s) identification

Physical hazards Not classified.

Serious eye damage/eye irritation **Health hazards** Category 2

Reproductive toxicity Effects on or via lactation

Environmental hazards

OSHA defined hazards

Not classified.

Label elements Not classified.



Signal word Warning

Causes serious eye irritation. May cause harm to breast-fedchildren. **Hazard statement**

Precautionary statement

Prevention Obtain special instructions before use. Do not breathe mist or vapor. Avoid contact during

pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using

this product. Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present Response

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Take off contaminated clothing and wash it before

reuse. IF exposed or concerned: Get medical advice/attention.

Storage Store in accordance with local/regional/national/international regulation. Store in a well-ventilated

area. Keep container tightly closed. Protect from sunlight. Store away from incompatible

materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

RelaTECH Premium Soluble 2550B SDS #: 342

Revision Date: May 27, 2016

1/10

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM		64742-52-5	60 - 100
C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN		63449-39-8	5 - 10
DIETHYLENE GLYCOL		111-46-6	0.5 - 1.5
PETROLEUM SULFONIC ACID, SODIUM SALT		68608-26-4	0.5 - 1.5
2-BUTOXYETHANOL		111-76-2	0.1 - 1
Other components below reportable levels	·		7 - 13

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing Skin contact

and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head Ingestion

low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel

unwell.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention.

During fire, gases hazardous to health may be formed.

Direct contact with eyes may cause temporary irritation.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting

General fire hazards

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathefumes.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe mist or vapor. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. To maintain product quality, do not store in heat or direct sunlight. Store in original tightly closed container. Room temperature - normal conditions. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

V-1--

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	PEL	5 mg/m3	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910 1	000)	
CO. CONA TUDIC 2 1 Ellinto for All	Type	Value	
2-BUTOXYETHANOL (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
U.S NIOSH		• •	
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	STEL	10 mg/m3	
· · · · · · · · · · · · · · · · · · ·	TWA	5 mg/m3	
US. NIOSH: Pocket Guide to Chen	nical Hazards	3	
	Туре	Value	
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
ACGIH			
7.0 0	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	TWA	5 mg/m3	

US. ACGIH Threshold Limit Values

Type Value

2-BUTOXYETHANOL (CAS TWA 20 ppm

111-76-2)

Exposure guidelines

US - California OELs: Skin designation

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-BUTOXYETHANOL (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR1910.1000)

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile.

Other Wear suitable protective clothing and gloves. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance AMBER
Physical state Liquid.
Form Liquid.
Color Blue.

OdorCHEMICAL NotOdor thresholdavailable. NotpHApplicable < 32Melting point/freezing point $^{\circ}$ F (< 0 $^{\circ}$ C)

Initial boiling point and boiling

range

> 212 °F (> 100 °C)

Flash point > 350 °F (> 160 °C) Cleveland Open Cup

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies) 100 % Water Miscible

Partition coefficient

Not available.

(n-octanol/water)

(II-octailoi/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

pH in aqueous solution 9.4 @ 5% Specific gravity 0.98 VOC ASTM D2369 16 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

occur.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Avoid contact with oxidizers or reducing agents.

Hazardous decomposition

products

Smoke, fumes, hydrogen chloride, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May be harmful if swallowed and enters airways. Droplets of the product aspirated into the lungs

through ingestion or vomiting may cause a serious chemical pneumonia. Expected to be a low

ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components Species Test Results

2-BUTOXYETHANOL (CAS 111-76-2)

Acute

Dermal

LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours

Rat 450 ppm, 4 Hours

Oral

LD50 Guinea pig 1.2 g/kg

 Mouse
 1.2 g/kg

 Rabbit
 0.32 g/kg

 Rat
 560 mg/kg

DIETHYLENE GLYCOL (CAS 111-46-6)

Acute

Dermal

LD50 Rabbit 11890 mg/kg

RelaTECH Premium Soluble 2550B SDS #: 342

Revision Date: May 27, 2016

Components	Species	Test Results
Oral		
LD50	Cat	3300 mg/kg
	Dog	9000 mg/kg
	Guinea pig	8700 mg/kg
	Mouse	13.3 g/kg
	Rabbit	26.9 g/kg
	Rat	12565 mg/kg
SEVERELY-HYDROTREAT	TED NAPHTHENIC PETROLEUM (CAS 64	1742-52-5)
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Rat	5.7 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg

Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin. Skin corrosion/irritation

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-BUTOXYETHANOL (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Contains a substance which causes risk of hazardous effects to the environment. Toxic to aquatic

life with long lasting effects.

Test Results Components **Species**

2-BUTOXYETHANOL (CAS 111-76-2)

Aquatic

Fish LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN (CAS 63449-39-8)

Aquatic

Fish LC50 Bluegill (Lepomis macrochirus) > 0.1 mg/l, 96 hours

DIETHYLENE GLYCOL (CAS 111-46-6)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) > 32000 mg/l, 96 hours

RelaTECH Premium Soluble 2550B SDS #: 342

Components Species Test Results

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Aquatic

Acute

Fish LC50 Fish > 100 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-BUTOXYETHANOL 0.83

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number Not Regulated UN proper shipping name Not Regulated

Transport hazard class(es)

Class Not Regulated

Subsidiary risk Label(s) Packing group

Environmental hazards

Marine pollutant Not Regulated (See below)

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions
Packaging exceptions
Packaging non bulk
Packaging bulk

Supplemental Information: 49CFR 171.4 excludes "non-bulk" packages (119 gallons or less) from Marine Pollutant Requirements unless all or part of the shipment is by vessel.

Revision Date: May 27, 2016

IATA

UN number Not regulated in small packages

UN proper shipping name

Transport hazard class(es)

Class

Subsidiary risk Packing group

Environmental hazards

ERG Code

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

^{*} Estimates for product may be based on additional component data not shown.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN number Not regulated (in small containers)

UN proper shipping name

Transport hazard class(es)

Class

Subsidiary risk

Packing group

Environmental hazards

Marine pollutant

EmS

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

General information

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

2-BUTOXYETHANOL (CAS 111-76-2)

US. New Jersey Worker and Community Right-to-Know Act

2-BUTOXYETHANOL (CAS 111-76-2)

US. Pennsylvania Worker and Community Right-to-Know Law

2-BUTOXYETHANOL (CAS 111-76-2) DIETHYLENE GLYCOL (CAS 111-46-6)

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 105 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 71 % to maintain compliance.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico *A "Yes" indicates this product co	Toxic Substances Control Act (TSCA) Inventory implies with the inventory requirements administered by the governing country	Yes y(s)

RelaTECH Premium Soluble 2550B SDS #: 342

Revision Date: May 27, 2016

16. Other information, including date of preparation or last revision

Issue date 05-27-2016

Revision date

Version # 01

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information OSHA Hazard Communication Standard 29 CFR 1910.1200 and GHS

RelaTECH Premium Soluble 2550B SDS #: 342

Revision Date: May 27, 2016