SAFETY DATA SHEET



1. Identification

RelaTECH Soluble Oil 100 Product identifier

Other means of identification 951620100SO

SDS number METALWORKING FLUID

Recommended use

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

RelaDyne, LLC Company name

9395 Kenwood Rd, Suite 104

Blue Ash. OH 45242

www.reladyne.com

888-830-3156

None known

Telephone (General

Information)

Recommended restrictions

Emergency telephone

number

INFOTRAC 800-535-5053

Emergency telephone number (outside USA)

2. Hazard(s) identification

Physical hazard Not classified

Serious eve damage/eve irritation **Health hazards**

Not classified Not classified

Environmental hazards OSHA defined hazards

Category 2



WARNING! Signal word

Causes serious eve irritation **Hazard statement**

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear **Precautionary statement**

protective gloves/protective clothing/eye protection/face protection. Prevention

> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

Advice or attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable

breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash

before reuse. Collect spillage.

Store in a well ventilated place. Keep container tightly closed. Protect from sunlight. Store away Storage

from incompatible materials. Store in accordance with local/regional/national/international

regulation.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

Response

classified (HNOC)

None known

None Supplemental information

Material name: RelaTECH Soluble Oil 100 SDS #: 343

Version #: 01 Issue date: 05-27-2016 1/8

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM		64742-52-5	60 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

Skin contact Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing

and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

> present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Rinse mouth thoroughly. Do not give liquids. Never give anything by mouth to a victim who is

unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Most important symptoms/effects, acute and delaved

Ingestion

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemicals. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire fighting

equipment/instructions

Specific methods

General fire hazards

Wear suitable protective equipment.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: RelaTECH Soluble Oil 100 SDS #: 343

Version #: 01 Issue date: 05-27-2016 2/8

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities To maintain product quality, do not store in heat or direct sunlight. Store in original tightly closed container. Room temperature - normal conditions. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	PEL	5 mg/m3	
U.S NIOSH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	
ACGIH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	TWA	5 mg/m3	

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is Eye/face protection

recommended.

Skin protection

Use protective gloves made of: Nitrile. Hand protection

Wear suitable protective clothing and gloves. Other

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Material name: RelaTECH Soluble Oil 100 SDS #: 343 3/8 Version #: 01 Issue date: 05-27-2016

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

9. Physical and chemical properties

Clear amber **Appearance**

Physical state Liquid **Form** Liquid Color Amber

Odor **PETROLEUM** Odor threshold Not available. рH 8.8-9.3 Typical Melting point/freezing point < 32 °F (< 0 °C) Initial boiling point and boiling > 212 °F (> 100 °C)

range

350 °F (176.7 °C) Cleveland Open Cup Flash point

Like water when diluted **Evaporation rate**

Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits Not available Flammability limit - lower

(%)

Flammability limit - upper

Not available

(%)

Not available Explosive limit - lower (%) Explosive limit - upper (%) Not available Vapor pressure Not available Not available Vapor density Relative density .958 kg/m3

Solubility(ies) 100 % Water Miscible

Partition coefficient

(n-octanol/water)

Not available

Not available **Auto-ignition temperature Decomposition temperature** Not available Not available **Viscosity**

Other information

9.1 @ 5% pH in aqueous solution Specific gravity 0.94 VOC ASTM D2369 10 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

Conditions to avoid Heat, flames and sparks. Temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Avoid contact with oxidizers or reducing agents.

Hazardous decomposition Smoke, fumes, and oxides of carbon

products

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. May be harmful if swallowed and enters airways. Inhalation

Material name: RelaTECH Soluble Oil 100 SDS #: 343 4/8 Version #: 01 Issue date: 05-27-2016

Skin contact May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

Eye contact Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components Species Test Results

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat 5.7 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Material name: RelaTECH Soluble Oil 100

Version #: 01 Issue date: 05-27-2016

^{*} Estimates for product may be based on additional component data not shown.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary

injury or death.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Aquatic

Acute

Fish LC50 Fish

> 100 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Mobility in soil No data available.

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsConsult authorities before disposal. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

Dispose in accordance with all applicable regulations.

lazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

Not regulated as dangerous goods. Not regulated by D.O.T.

IATA

Not regulated as dangerous goods. Not regulated by D.O.T.

IMDG

Not regulated as dangerous goods. Not regulated by D.O.T.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

Material name: RelaTECH Soluble Oil 100 SDS #: 343

Version #: 01 Issue date: 05-27-2016

^{*} Estimates for product may be based on additional component data not shown.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories**

Delayed Hazard -Nο Fire Hazard -No Pressure Hazard -No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Yes

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed

US. Rhode Island RTK

Not regulated.

Quality Management

District (SCAQMD) Rule 1144 (VOC Emissions)

California South Coast Air This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 95 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 79

% to maintain compliance.

SDS #: 343

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region Inventory name On inventory or exempt (yes/no)* Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No

Material name: RelaTECH Soluble Oil 100

Version #: 01 Issue date: 05-27-2016

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 05-27-2016

Revision date


Version # 01

Further information

Label requirements WARNING!

CAUSES EYE AND SKIN IRRITATION

MAY CAUSE RESPIRATORY TRACT IRRITATION



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Material name: RelaTECH Soluble Oil 100 SDS #: 343

Yes