

# Safety Data Sheet

according to OSHA Hazard Communication  
29 CFR Part 1910.1200



## SECTION 1. Identification

**Product Code** 99018soLVMS  
**Product Name:** Mineral Spirits, Odorless

**Supplied by:** RelaDyne, LLC  
9395 Kenwood Rd, Suite 104  
Blue Ashe, OH 45242  
888-830-3156  
www.reladyne.com

**24 Hour Emergency:**  
**INFOTRAC: 1-800-535-5053**

NOTE: INFOTRAC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals

## SECTION 2. Hazard(s) Identification

\*\*\* EMERGENCY OVERVIEW \*\*\*: Flammable liquid and vapor.

### GHS Classification

Asp. Tox. 1, Flam. Liq. 3

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

Flammable Liquid, category 3

H226

Flammable liquid and vapor.

Aspiration Hazard, category 1

H304

May be fatal if swallowed and enters airways.

### GHS PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use appropriate method to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**SECTION 3. Composition/Information on Ingredients**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Synthetic isoparaffinic hydrocarbon	64742-48-9	75-100	GHS02-GHS08	H226-304

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

**SECTION 4. First-Aid Measures**

**FIRST AID - EYE CONTACT:** Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

**FIRST AID - SKIN CONTACT:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

**FIRST AID - INHALATION:** Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

**FIRST AID - INGESTION:** Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

**SECTION 5. Fire-Fighting Measures**

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

**SPECIAL FIREFIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

**EXTINGUISHING MEDIA:** Dry Chemical, Foam, Water Fog

**SECTION 6. Accidental Release Measures**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.)Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section)Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

**SECTION 7. Handling and Storage**

**HANDLING:** Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all SDS/label precautions even after containers are emptied because they may retain product residues.

**STORAGE:** Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight. Static Discharge, materials can accumulate static charges which can cause an incendiary electrical discharge. Material is a static accumulator which has the potential of forming ignitable vapor-air mixtures in storage tanks.

## SECTION 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH-TLV-TWA</u>	<u>ACGIH-TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Synthetic isoparaffinic hydrocarbon	400 ppm	N.D.	400 ppm	N.D.

### Personal Protection



**RESPIRATORY PROTECTION:** NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.



**SKIN PROTECTION:** Wear impervious gloves to prevent contact with the skin. Wear long sleeves when contact is likely to occur. Wear protective gear as needed - apron, suit, boots.



**EYE PROTECTION:** Wear safety glasses with side shields (or goggles) and a face shield.



**OTHER PROTECTIVE EQUIPMENT:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



**HYGIENIC PRACTICES:** Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

## SECTION 9. Physical and Chemical Properties

<b>Appearance:</b>	Clear, colorless liquid	<b>Physical State:</b>	Liquid
<b>Odor:</b>	Typical	<b>Odor Threshold:</b>	N.D.
<b>Density, g/cm<sup>3</sup>:</b>	0.761	<b>pH:</b>	N.D.
<b>Freeze Point, °F:</b>	N.D.	<b>Viscosity:</b>	N.D.
<b>Solubility in Water:</b>	Negligible	<b>Explosive Limits, vol%:</b>	0.7 - 5.4
<b>Boiling Range, °F:</b>	356 - 370	<b>Flash Point, °F:</b>	129
<b>Evaporation Rate:</b>	0.1	<b>Auto-ignition Temp., °F:</b>	N.D.
<b>Vapor Density:</b>	N.D.	<b>Vapor Pressure:</b>	0.075 kPa @ 20 C

(See "Other information" Section for abbreviation legend)

## SECTION 10. Stability and Reactivity

**STABILITY:** No Information

**CONDITIONS TO AVOID:** Avoid impact, friction, heat, sparks, flame and source of ignition.

**INCOMPATIBILITY:** Prevent contact with strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Toxic gases/fumes are given off during burning or thermal decomposition. During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed.

**HAZARDOUS POLYMERIZATION:** No Information

## SECTION 11. Toxicological Information



### Information on Toxicological Effects

**EFFECTS OF OVEREXPOSURE - INHALATION:** Prolonged inhalation may be harmful. Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression).

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Contact with skin may cause mild irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** May cause eye irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** May be fatal if swallowed. Harmful or fatal if liquid is aspirated into lungs. Ingestion and/or vomiting may cause aspiration into the lungs resulting in chemical pneumonitis (inflammation of the lungs). May cause pulmonary edema.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

**Primary Route(s) of Entry:** Eye Contact, Ingestion, Inhalation, Skin Contact

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	<u>Vapor LC50, mg/L</u>
64742-48-9	Synthetic isoparaffinic hydrocarbon	>10,000	>5000	>20.0

## SECTION 12. Ecological Information

**ECOLOGICAL INFORMATION:** No Information

## SECTION 13. Disposal Considerations



For more guidance and information contact our Waste Services Division at (262) 658-4000.

Always dispose of any waste in accordance with all local, state, and federal regulations.

**DISPOSAL METHOD:** Dispose of waste in accordance with all local, state and federal regulations.

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED:** Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.)Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section)Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Remove from surface by skimming or with suitable absorbents. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

## SECTION 14. Transport Information

<b>DOT Proper Shipping Name:</b>	Petroleum distillates, n.o.s. (naphtha solvent) - Combustible Liquid	<b>Packing Group:</b>	III
<b>DOT Hazard Class:</b>	No Information	<b>Hazard SubClass:</b>	No Information
<b>DOT UN/NA Number:</b>	UN1268	<b>Resp. Guide Page:</b>	128

## SECTION 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

**TOXIC SUBSTANCES CONTROL ACT:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

**U.S. State Regulations:****NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

**International Regulations: As follows -****CANADIAN WHMIS:**

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

**WHMIS Class:** No Information

**SECTION 16. Other Information**

**Revision Date:** 06/30/2015 **Supersedes Date:** New SDS

**Datasheet produced by:** EH&S - Regulatory Department

**HMIS Ratings:**

<b>Health:</b>	1	<b>Flammability:</b>	2	<b>Reactivity:</b>	0	<b>Personal Protection:</b>	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

**Volatile Organic Compounds, gr/ltr:** 100

DISCLAIMER: This Safety Data Sheet is prepared according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. The information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.