## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 05/29/2015 Revision date: 05/29/2015 Version: 1.0



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : DuraMAX DM452 High VOC Non-chlorinated Brake Parts Cleaner

Product code : 95076NCBCHV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake cleaner.

1.3. Details of the supplier of the safety data sheet

RelaDyne 9395 Kenwoo

9395 Kenwood Rd., Suite 104 Blue Ash, OH 45242

www.reladyne.com

1.4. Emergency telephone number

Emergency number : INFOTRAC 800-535-5053

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Flammable Aerosol 1

Gases Under Pressure - Compressed gas

Skin irritation 2

Reproductive toxicity 2 (developmental)

Specific target organ toxicity - Single exposure 3

Specific target organ toxicity - Repeated exposure 2

Aspiration hazard 1

#### 2.2. Label elements

## **GHS-US** labelling

Hazard pictograms (GHS-US)



 $\langle \! \rangle$ 





Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of damaging the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US)

: Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe gas/mist/vapors/spray. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 2.3. Other hazards

No additional information available

## 2.4. Unknown acute toxicity (GHS-US)

76 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

DuraMAX DM452 High VOC Non-chlorinated Brake Parts Cleaner SDS# 452

Revision Date: May 29, 2015

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Heptane, branched, cyclic and linear	(CAS No) 426260-76-6	60 - 100	Flam. Liq. 2 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
n-Heptane	(CAS No) 142-82-5	20 - 50	Flam. Liq. 2 Skin Irrit. 2 STOT SE 3 Asp. Tox. 1
Toluene	(CAS No) 108-88-3	1 - 5	Flam. Liq. 2 Skin Irrit. 2 Repr. 2 (developmental) STOT SE 3 STOT RE 2 Asp. Tox. 1
Carbon dioxide	(CAS No) 124-38-9	1 - 5	Compressed gas

<sup>\*</sup> The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures after inhalation : If inha

: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous system depression.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

## 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

#### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

#### 5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

#### 6.2. Methods and material for containment and cleaning up

For containment

: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up

: Scoop up material and place in a disposal container. Provide ventilation.

#### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from sources of ignition. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid contact with skin and eyes. Do not breathe gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

#### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Heptane, branched, cyclic and linear (426260-76-6)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

n-Heptane (142-82-5)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	2000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm

Carbon dioxide (124-38-9)		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

#### 8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear chemically resistant protective gloves.

DuraMAX DM452 High VOC Non-chlorinated Brake Parts Cleaner

Revision Date:

SDS# 452 3 of 6 May 29, 2015

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Safety glasses or goggles are recommended when using product. Eye protection

Skin and body protection : Wear suitable protective clothing.

A NIOSH approved respirator is recommended in poorly ventilated areas or when permissible Respiratory protection

exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls Maintain levels below Community environmental protection thresholds.

> No data available No data available

> No data available

No data available

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully Other information

before eating or smoking. Handle according to established industrial hygiene and safety practices.

## **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties

Physical state : Gas/Pressurized Liquid

Appearance Clear Color Colorless Solvent Odor

Odor threshold : No data available No data available Relative evaporation rate (butylacetate=1) : No data available Melting point No data available Freezing point No data available Boiling point : No data available Flash point No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Flammability (solid, gas) Flammable Vapor pressure No data available Relative vapor density at 20 °C No data available Relative density : 0.7825 - 0.7855 : No data available Solubility Log Pow No data available Log Kow : No data available Viscosity, kinematic No data available

#### Other information

No additional information available

### **SECTION 10: Stability and reactivity**

## Reactivity

Viscosity, dynamic

**Explosive limits** 

Explosive properties Oxidising properties

No dangerous reaction known under conditions of normal use.

## **Chemical stability**

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

#### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### **Conditions to avoid**

Heat. Incompatible materials. Sources of ignition.

#### Incompatible materials

Strong oxidizing agents. Strong reducing agents.

#### **Hazardous decomposition products**

May include, and are not limited to: oxides of carbon.

DuraMAX DM452 High VOC Non-chlorinated Brake Parts Cleaner SDS# 452 4 of 6 May 29, 2015

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

<b>SECTION 11: To</b>	xicologica	al information
<u></u>		ar irriorrination

11.1.	Information on	

Acute toxicity : Not classified

DM452	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5 mg/l/4h

n-Heptane (142-82-5)	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	103 g/m³/4h

Toluene (108-88-3)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	12124 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	28.1 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Based on available data, the classification criteria are not met.

Toluene (108-88-3)		
	IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging the unborn child. Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : May cause respiratory tract irritation. May cause drowsiness, dizziness and central nervous

system depression.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with possible redness and swelling.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and

cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

DM452	
Persistence and degradability	Not established.

## 12.3. Bioaccumulative potential

DM452	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

DuraMAX DM452 High VOC Non-chlorinated Brake Parts Cleaner SDS# 452 5 of 6

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

## **SECTION 13: Disposal considerations**

Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal

regulations. The generation of waste should be avoided or minimized wherever possible.

: Flammable vapors may accumulate in the container. Do not incinerate closed containers. Additional information

#### **SECTION 14: Transport information**

In accordance with DOT

14.1. **UN** number

UN-No. UN1950

14.2. **UN** proper shipping name

Proper Shipping Name : Aerosols, flammable

**Hazard Classes** 2.1

Hazard labels



14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

n-Heptane (142-82-5)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Toluene (108-88-3)	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 %


### 15.3. US State regulations

NFPA reactivity

DM452	
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth
	defects or other reproductive harm.

## **SECTION 16: Other information**

Indication of changes : None. Date of issue : 05/29/2015 Other information : None. NFPA health hazard 2 NFPA fire hazard 4



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

0