

Issue Date: 01-April-2015

Revision Date: 5-June-2018

1. IDENTIFICATION

Product Identifier

Product Name DuraMAX RV Antifreeze -50 Degrees

Other means of identification

SDS # 95082CH355P, 95082CH416R, 95082CH430R

Recommended use of the chemical and restrictions on use

Recommended Use Pipe anti-freeze.

Manufactured for

RelaDyne, LLC
 8280 Montgomery Road, Suite 101
 Cincinnati, OH 45236
 888-830-3156
 www.reladyne.com

Emergency Telephone Number

Emergency Telephone (24 hr) INFOTRAC 800-535-5053

2. HAZARDS IDENTIFICATION

Physical State Red Liquid

Classification

Acute toxicity - Inhalation (Gases)	Category 4
Carcinogenicity	Category 1A

Signal Word

Danger

Hazard Statements

Harmful if inhaled
 May cause cancer



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethyl Alcohol	64-17-5	10-20
Glycerol	56-81-5	1-10
2-Propanol	67-63-0	1-10
Methyl alcohol	67-56-1	<1
Methylisobutyl ketone	108-10-1	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

Symptoms	Harmful if inhaled. May cause cancer.
-----------------	---------------------------------------

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
Glycerol 56-81-5	-	TWA: 15 mg/m ³ mist, total particulate TWA: 5 mg/m ³ mist, respirable fraction (vacated) TWA: 10 mg/m ³ mist, total particulate (vacated) TWA: 5 mg/m ³ mist, respirable fraction	-
2-Propanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methylisobutyl ketone 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m ³ STEL: 75 ppm STEL: 300 mg/m ³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Avoid contact with eyes.

Skin and Body Protection Wear suitable protective clothing.

Respiratory Protection Ensure adequate ventilation, especially in confined areas.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Not determined
Appearance	Clear Red Liquid	Odor Threshold	Not determined
Color	Red		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	7.67	
Melting Point/Freezing Point	Not determined	
Boiling Point/Boiling Range	Not determined	
Flash Point	Not determined	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Upper Flammability Limits	Not determined	
Lower Flammability Limit	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Specific Gravity	.974 - .990	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

Eye Contact	Avoid contact with eyes.
Skin Contact	Avoid contact with skin.
Inhalation	Harmful if inhaled.
Ingestion	Do not ingest.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl Alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
Glycerol 56-81-5	= 12600 mg/kg (Rat)	> 10 g/kg (Rabbit)	> 570 mg/m ³ (Rat) 1 h
1,2 Propanediol 57-55-6	= 20000 mg/kg (Rat)	= 20800 mg/kg (Rabbit)	-
2-Propanol 67-63-0	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rat) = 12870 mg/kg (Rabbit)	= 72.6 mg/L (Rat) 4 h
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 83.2 mg/L (Rat) 4 h = 64000 ppm (Rat) 4 h
Methylisobutyl ketone 108-10-1	= 2080 mg/kg (Rat)	> 16000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethyl Alcohol 64-17-5	A3	Group 1	Known	X
2-Propanol 67-63-0		Group 3		X
Methylisobutyl ketone 108-10-1	A3	Group 2B		X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethyl Alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static
Glycerol 56-81-5		51 - 57: 96 h Oncorhynchus mykiss mL/L LC50 static		
1,2 Propanediol 57-55-6	19000: 96 h Pseudokirchneriella subcapitata mg/L EC50	51600: 96 h Oncorhynchus mykiss mg/L LC50 static 41 - 47: 96 h Oncorhynchus mykiss mL/L LC50 static 51400: 96 h Pimephales promelas mg/L LC50 static 710: 96 h Pimephales promelas mg/L LC50		10000: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50 Static
2-Propanol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow- through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50		13299: 48 h Daphnia magna mg/L EC50
Methyl alcohol 67-56-1		28200: 96 h Pimephales promelas mg/L LC50 flow- through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
Methylisobutyl ketone 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow- through	EC50 = 79.6 mg/L 5 min	170: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Ethyl Alcohol 64-17-5	-0.32
Glycerol 56-81-5	-1.76
2-Propanol 67-63-0	0.05
Methyl alcohol 67-56-1	-0.77
Methylisobutyl ketone 108-10-1	1.19

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol 67-56-1		Included in waste stream: F039		U154
Methylisobutyl ketone 108-10-1		Included in waste stream: F039		U161

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Ethyl Alcohol 64-17-5	Toxic Ignitable
2-Propanol 67-63-0	Toxic Ignitable
Methyl alcohol 67-56-1	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG
Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethyl Alcohol	Present	X		Present		Present	X	Present	X	X
Glycerol	Present	X		Present		Present	X	Present	X	X
2-Propanol	Present	X		Present		Present	X	Present	X	X
Methyl alcohol	Present	X		Present		Present	X	Present	X	X
Methylisobutyl ketone	Present	X		Present		Present	X	Present	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl alcohol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Methylisobutyl ketone 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
2-Propanol - 67-63-0	67-63-0	1.5	1.0

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl Alcohol - 64-17-5	Carcinogen Developmental
Methyl alcohol - 67-56-1	Developmental
Methylisobutyl ketone - 108-10-1	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethyl Alcohol 64-17-5	X	X	X
Glycerol 56-81-5	X	X	X
1,2 Propanediol 57-55-6	X		X
2-Propanol 67-63-0	X	X	X
Methyl alcohol 67-56-1	X	X	X
Chemical Name	New Jersey	Massachusetts	Pennsylvania

Methylisobutyl ketone 108-10-1	X	X	X
-----------------------------------	---	---	---

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	0	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	0	1	0	B

Issue Date: 01-April-2015
Revision Date: 5-June-2018
Revision Note: Updated Section 1

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet