



PRODUCT DATA SHEET

DuraMAX[®] DEXRON[®]-VI ATF

AUTOMATIC TRANSMISSION FLUID



PRODUCT DESCRIPTION




DuraMAX[®] DEXRON[®]-VI ATF is a premium full synthetic transmission fluid designed to meet General Motors DEXRON[®]-VI requirements for use in 6+ speed automatic transmissions found in model year 2006 and newer. Its low-viscosity formula provides enhanced performance compared to older generation DEXRON fluids.

PRODUCT APPLICATION

DuraMAX DEXRON-VI ATF is recommended for use in 2006 and new General Motors 6-speed automatic transmissions as well as previous generation models where DEXRON-III(H), III(G) and II(E) fluids would have been recommended.

It is also suitable for use in many Honda, Hyundai, Toyota and other import vehicles where low-viscosity automatic transmission fluids are recommended.

** - This product is not recommended for use in CVT or dual-clutch transmissions, or where ultra low viscosity (ULV), Ford Type F, MERCON V, MERCON SP transmission fluids are specified*



SPECIFICATIONS

GM DEXRON[®]-VI (GMW 16444) (license # J-60450)
Ford Mercon[®]-LV



TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	DEXRON-VI
Viscosity @ 40°C (cSt)	ASTM D445	28.7
Viscosity @ 100°C (cSt)	ASTM D445	5.8
Viscosity Index	ASTM D2270	150
Brookfield Viscosity @ -40°C. cP	ASTM D2983	10,300
Rust Protection	ASTM D665A	Pass
Hydrolytic Stability Test	ASTM D2619	Pass
Pour Point, °C/°F	ASTM D5950	-51/-60
Flash Point, °C/°F	ASTM D92	220/428
Color	ASTM D1500	Red

This product is not expected to have any adverse health implications when used for its intended purposes. Always wear protective gloves when handling used oil and dispose of properly. Avoid contact with skin and wash immediately with soap and water should any contact occur. Always follow manufacturers recommendations for fluid viscosity and service category. RelaDyne assumes no responsibility for product misuse or improper application. For a copy of this product's Safety Data Sheet (SDS), visit www.RELADYNE.com Rev (0425-D1)

FEATURES AND BENEFITS

DuraMAX DEXRON-VI ATF is built using full synthetic base stocks, advanced performance additives and specialized polymeric molecules to extended service life and improved transmission performance compared to previous generation DEXRON transmission fluids.

- Low viscosity chemistry helps improve transmission performance and fuel efficiency compared to standard viscosity products
- Approved by General Motors for DEXRON-VI applications including vehicles still under original factory warranty
- Shear stable formula helps the fluid maintain proper viscosity and resists unwanted thinning and thickening due to high operating temperatures and cold starts/shifts
- Enhanced friction modifiers ensure smooth shifting and unwanted shudder during extended service intervals
- Superior oxidation stability helps keep transmission components clean and reduces wear and vibration even in severe operating conditions
- Requires no supplemental transmission additives or top treats required



RelaDyne, LLC. | 8280 Montgomery Road, Suite 101 | Cincinnati, OH 45236 | 1-888-830-3156 | www.reladyne.com

