

# SAFETY DATA SHEET

1. Identification

RelaTECH All Cool 2500 Heavy

**Product identifier Other means** 

of identification

Not applicable

**SDS** number Recommended

METALWORKING FLUID

use

**Recommended restrictions** 

None known

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

RelaDyne, LLC Company name

RelaDyne, LLC

8280 Montgomery Road, Suite 101

Telephone (General

Cincinnati, OH 45236

Information)

888-830-3156

**Emergency telephone** 

www.reladyne.com

number

**Emergency telephone** number (outside USA) INFOTRAC 800-535-5053

2. Hazard(s) identification

Physical hazard

**Health hazards** Not classified Category 1 Category 2

**Environmental hazards** 

Serious eye damage/eye irritation

**OSHA** defined hazards Sensitization, skin

Not classified

Not classified



Signal word

WARNING! **Hazard statement** 

**Precautionary statement** 

Causes serious eye irritation. May cause an allergic skin reaction.

Prevention Response

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear

protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

Advice or attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash

before reuse. Collect spillage.

Store in a well ventilated place. Keep container tightly closed. Protect from sunlight. Store away Storage

from incompatible materials. Store in accordance with local/regional/national/international

regulation. **Disposal** 

Hazard(s) not otherwise

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known classified (HNOC)

Supplemental information None

Material name: RelaTECH All Cool 2500 Heavy SDS 251 

1/8

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
3-IODO-2-PROPYNYL BITYL CARBAMATE		Mixture	0.1-1.0
DIETHYLENE GLYCOL MONOBUTYL ETHER		112-34-5	1-5
HEXAHYDRO-1,3,5-TRIS (2-HYDROXETHYL)-S-TRIAZINE		4719-04-4	1-5

Other components below reportable levels

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret

#### 4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing Skin contact

and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

vision.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Rinse mouth thoroughly. Do not give liquids. Never give anything by mouth to a victim who is

unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and

delayed

Ingestion

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Indication of immediate medical attention and special

treatment needed **General information** 

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemicals. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to

local circumstances and the surrounding environment.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for firefighters

Fire fighting

equipment/instructions Specific methods

Wear suitable protective equipment.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: RelaTECH All Cool 2500 Heavy Version #: 01 Issue date: 04-08-2016

### Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

#### **Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.

### 7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities To maintain product quality, do not store in heat or direct sunlight. Store in original tightly closed container. Room temperature - normal conditions. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

### 8. Exposure controls/personal protection

### Occupational exposure limits

U.S. - OSHA

Thermal hazards

	Туре	Value			
ACGIH					
	Туре	Value			
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)	TWA	10 PPM			
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.				
Individual protection measures, such as personal protective equipment					
Eye/face protection	Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is recommended.				
Skin protection					
Hand protection	Use protective gloves made of: Nitr	ile.			
Other	Wear suitable protective clothing and gloves.				
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.				

Wear appropriate thermal protective clothing, when necessary.

Material name: RelaTECH All Cool 2500 Heavy Version #: 01 Issue date: 04-08-2016

**General hygiene** considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating. drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

Clear **Appearance** Physical state Liquid **Form** Liquid Color Amber Mild Odor

Odor threshold Not available. рH 9.0-9.3 Typical Melting point/freezing point < 32 °F (< 0 °C) Initial boiling point and boiling > 212 °F (> 100 °C)

range

Flash point Not applicable

**Evaporation rate** Like water when diluted

Not applicable Flammability (solid, gas) Upper/lower flammability or explosive limits Not available Flammability limit - lower

(%)

Not available

Flammability limit - upper (%)

Not available Explosive limit - lower (%) Explosive limit - upper (%) Not available

Vapor pressure Not available Not available Vapor density Relative density Not available

100 % Water Miscible Solubility(ies)

**Partition coefficient** 

(n-octanol/water)

Not available

Not available **Auto-ignition temperature** Not available **Decomposition temperature** Not available **Viscosity** 

Other information

9.0 @ 5% pH in aqueous solution Specific gravity 0.97 VOC ASTM D2369 15 %

### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** 

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

Conditions to avoid Heat, flames and sparks. Temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Avoid contact with oxidizers or reducing agents.

Hazardous decomposition

Smoke, fumes, and oxides of carbon

products

### 11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. May be harmful if swallowed and enters airways. Inhalation

Material name: RelaTECH All Cool 2500 Heavy 

**Skin contact** May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

Eye contact Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

#### Information on toxicological effects

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components Species Test Results

DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5

Dermal

 LD 50
 Rabbit
 2700 mg/kg

 Oral
 Guinea Pig
 2000 mg/kg

3-IODO-2-PROPYNYL BUTYLCARBAMATE (CAS 55406-53-6)

Dermal

LD50 Rabbit >2000 mg/kg

Oral

LD50 Rat 1.1 g/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.

Serious eye damage/eye

irritation

Causes serious eye irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary

injury or death.

**Chronic effects** Prolonged inhalation may be harmful.

### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

#### Aquatic

Acute None Listed

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions**Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

### 14. Transport information

DOT

Not regulated as dangerous goods. Not regulated by D.O.T.

IATA

Not regulated as dangerous goods. Not regulated by D.O.T.

**IMDG** 

Not regulated as dangerous goods. Not regulated by D.O.T.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

Material name: RelaTECH All Cool 2500 Heavy

SDS 251

### 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYTHYL)-S-TRIAZINE (CAS 4719-04-4) 1.0% One time export notification only

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

### SARA 304 Emergency release notification

Not regulated.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** 

Delayed Hazard -Nο Fire Hazard -No Pressure Hazard -No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

#### SARA 313 (TRI reporting)

DIETHYLENE GLYCOL MONOBUTYL ETHER CAS 112-34-5 1-5 % BY WEIGHT 3-IODO-2-PROPYNYL BUTYLCARBAMATE CAS 55406-53-6 0.1-1.0% BY WEIGHT

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**FDA** Not regulated.

US state regulations

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### **US. Massachusetts RTK - Substance List**

Not regulated.

#### US. New Jersey Worker and Community Right-to-Know Act

### US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

#### **US. Rhode Island RTK**

Not regulated.

**Quality Management** 

District (SCAQMD) Rule 1144 (VOC Emissions)

California South Coast Air This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 73 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 100 % to maintain compliance.

### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

### International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Material name: RelaTECH All Cool 2500 Heavy Version #: 01 Issue date: 04-08-2016

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory Yes \*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

## 16. Other information, including date of preparation or last revision


04-08-2016 Issue date **Revision date** 06-18-2018 Version # 01, RLD 2

**Further information** 

Label requirements **WARNING!** 

CAUSES EYE AND SKIN IRRITATION

MAY CAUSE RESPIRATORY TRACT IRRITATION



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDS's under 29 CFR 1910.1200, the preparer may choose to provide them.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision Information** 06/18/2018 revision updated Section 1

Material name: RelaTECH All Cool 2500 Heavy SDS 251 8/8

Version #: 01 Issue date: 04-08-2016