

SAFETY DATA SHEET

1. Identification **Product identifier**

Premier 600 Synthetic Coolant

SYNTHETIC METALWORKING FLUID

Other means of identification

Not applicable SDS number

METALWORKING FLUID Recommended use

None known. **Recommended restrictions**

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Reladyne, LLC 8280

Montgomery Road, Suite 101

Cincinnati, OH 45236

Telephone (General

Information)

888-830-3156

Emergency telephone

number 888-535-5053

2. Hazard(s) identification

Skin corrosion/irritation Category 1 **Physical hazards** Category 1 Serious eye damage/eye irritation Health hazards Sensitization, skin Category 1

> Not classified. Not classified.

Environmental hazards OSHA defined hazards

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Precautionary statement

Prevention

Keep only in original container. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash

thoroughly after handling. Wear protective gloves. Wear eye/face protection.

Response IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If swallowed: Call a poison center/doctor if you feel unwell. Take off

SDS US

contaminated clothing and wash it before reuse.

Storage Protect from sunlight. Store in a closed container. Store away from incompatible materials. Store

in accordance with local/regional/national/international regulation.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: Premier 600 Synthetic

Coolant Version #: 02 Issue date: 1/8

06-01-2015

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
TRIETHANOLAMINE		102-71-6	10 - 30
HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S- TRIAZINE		4719-04-4	0.1 - 1

Other components below reportable levels

60 - 100

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. If exposed or

concerned: Get medical advice/attention.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

Special protective equipment and precautions for firefighters

the chemical

Fire fighting

equipment/instructions

Specific methods

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2). Water.

Not applicable, non-combustible.

Not available.

During fire, gases hazardous to health may be formed.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb spillage to prevent material damage. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

Material name: Premier 600 Synthetic Coolant SDS US

Version # 02 Issue date: 06-01-2015 2/8

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

7. Handling and storage

Precautions for safe handling Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Provide adequate

ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene

practices.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in corrosive resistant container with a resistant inner liner. Keep only in the original container. Store away from incompatible materials

(see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. NIOSH: Pocket Guide to Chemical Hazards

	Туре	Value	Form
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	

Exposure guidelines

US - California OELs: Skin designation

None

US ACGIH Threshold Limit Values: Skin designation

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear suitable protective clothing and gloves.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Amber
Physical state Liquid.
Form Liquid.
Color Amber

Odor Chemical
Odor threshold Not available.

pH 9.0

Melting point/freezing point -10 °F (-23.3 °C)

Initial boiling point and boiling

range

06-01-2015

> 212 °F (> 100 °C) estimated

Flash point Not Applicable

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable.

Material name: Premier 600 Synthetic Coolant Version #: 02 Issue date:

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies) 100 % Water Miscible

Partition coefficient

(n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

pH in aqueous solution 9.0 Specific gravity 1.077 VOC ASTM D2369 15 %

10. Stability and reactivity

Reactivity Not Applicable

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Do not add sodium nitrite or other nitrosating agents which may form cancer causing

nitrosamines. Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

Smoke, fumes, oxides of nitrogen, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. May cause allergic skin reaction.

06-01-2015

Components **Species Test Results**

TRIETHANOLAMINE (CAS 102-71-6)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Guinea pig 5300 mg/kg

> Rat 8 g/kg

Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin. Skin corrosion/irritation

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not classified.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
DIETHANOLAMINE (CAS 111-42-2)		
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	61.8 - 86.04 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	100 mg/l, 96 hours
TRIETHANOLAMINE	(CAS 102-71-6)		
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	10610 - 13010 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

-1.43 **DIETHANOLAMINE TRIETHANOLAMINE** -1

Material name: Premier 600 Synthetic Coolant SDS US

5/8

^{*} Estimates for product may be based on additional component data not shown.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number Not Regulated In Drum Quantities **UN** proper shipping name Not Regulated in Drum Quantities Transport hazard class(es) Not Regulated in Drum Quantities

IATA

UN number Not Regulated **UN proper shipping name** Not Regulated Transport hazard class(es) Not Regulated

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN number **Not Regulated UN proper shipping name Not Regulated** Transport hazard class(es) Not Regulated

Marine pollutant No. F-A. S-B **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Material name: Premier 600 Synthetic Coolant SDS US

Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication.

Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311

and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

HEXAHYDRO-1,3,5-TRIS (2-HYDROXYETHYL)-S-1.0 % One-Time Export Notification only.

TRIAZINE (CAS 4719-04-4)

CERCLA Hazardous Substance List (40 CFR 302.4)

DIETHANOLAMINE (CAS 111-42-2) Listed.

SARA 304 Emergency release notification

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Material name: Premier 600 Synthetic Coolant SDS US

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. Massachusetts RTK - Substance List

TRIETHANOLAMINE (CAS 102-71-6)

US. New Jersey Worker and Community Right-to-Know Act

TRIETHANOLAMINE (CAS 102-71-6)

US. Pennsylvania Worker and Community Right-to-Know Law

TRIETHANOLAMINE (CAS 102-71-6)

US. Rhode Island RTK

DIETHANOLAMINE (CAS 111-42-2)

California South Coast Air **Quality Management** District (SCAQMD) Rule 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 108 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

NITRILOTRIACETIC ACID (CAS 139-13-9) Listed: January 1, 1988

is 69 % to maintain compliance.

International Inventories Country(s) or region

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision 6-01-2015

Issue date

Revision date

Version # 02

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Physical & Chemical Properties: Multiple Properties **Revision Information**

Material name: Premier 600 Synthetic

SDS US Coolant Version #: 02 Issue date:

06-01-2015

8/8