Safety Data Sheet

according to OSHA Hazard Communication 29 CFR Part 1910.1200



24 Hour Emergency:

Outside U.S. and Canada Infotrac: 1-800-535-5053

INFOTRAC: 1-800-535-5053

NOTE: INFOTRAC and National Response Center

emergency numbers to be used only in the event of

chemical emergencies involving a spill, leak, fire,

exposure or accident involving chemicals

SECTION 1. Identification

Product Code 95162205ED0	Product Code	95162205ED0	
--------------------------	--------------	-------------	--

- Product Name: RelaTECH Drawing Oil 205 E
- Supplied by: RelaDyne, LLC 8280 Montgomery Road, Suite 101 Cincinnati, OH 45236 888-830-3156 www.reladyne.com

SECTION 2. Hazard(s) Identification

*** EMERGENCY OVERVIEW ***: No Information

GHS Classification

Asp. Tox. 1, Eye Irrit. 2B, Skin Irrit. 2

Symbol(s) of Product



Signal Word Danger

GHS HAZARD STATEMENTS

Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye Irritation, category 2B	H320	Causes eye irritation
Skin Irritation, category 2	H315	Causes skin irritation.
GHS PRECAUTIONARY STATEMENTS		
P264	Wash thorou	ughly after handling.
P280	Wear protect	tive gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLO	WED: Immediately call a POISON CENTER/doctor/physician
P302+P352	IF ON SKIN	: Wash with plenty of water
P305+P351+P338		Rinse cautiously with water for several minutes. Remove contact lenses, if easy to do. Continue rinsing.
P321	Specific trea	atment (see first aid section on this label).
P331	Do NOT ind	uce vomiting.
P332+P313	lf skin irritati	on occurs: Get medical advice/attention.
P337+P313	If eye irritation	on persists: Get medical advice/attention.
P362+P364	Take off cor	taminated clothing and wash it before reuse.
P405	Store locked	1 up.
P501	Dispose of c regulations.	contents/container in accordance with local/regional/national/international

SECTION 3. Composition/Information on Ingredients

Chemical Name

Straight run middle distillate

CAS-No. <u>Wt. %</u> 64742-46-7

GHS Symbols GHS07-GHS08 75-100

GHS Statements H304-315-320

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

SECTION 4. First-Aid Measures



FIRST AID - EYE CONTACT: Remove contact lenses if worn. Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

FIRST AID - SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately and clean shoes before reuse. Clean or discard contaminated leather goods.

FIRST AID - INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

FIRST AID - INGESTION: Do not induce vomiting. Do not give liquids. Obtain emergency medical attention.

SECTION 5. Fire-Fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Avoid use of solid water streams. Water spray and foam must be applied carefully to avoid frothing. Use water spray to knock down vapors.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

SECTION 6. Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Use only noncombustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. If leak or spill has not ignited, use water spray to disperse the vapors. Do not touch or walk through spilled material. Stay upwind of spill. Ventilate spill area. Collect spilled materials for disposal. Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.)

SECTION 7. Handling and Storage



HANDLING: Use only in a well ventilated area. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor, fumes or mist.

STORAGE: Keep away from heat, sparks, and flame. Keep container closed when not in use. Protect from direct sunlight. Store containers in a cool, well ventilated place.

SECTION 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits					
Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING	
Straight run middle distillate	10 mg/m3	5 mg/m3	5 mg/m3	N.D.	

Personal Protection



RESPIRATORY PROTECTION: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.



SKIN PROTECTION: Wear impervious gloves to prevent contact with the skin. Wear protective gear as needed - apron, suit, boots.



EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.



OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.



HYGENIC PRACTICES: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and wash before reuse. Avoid breathing vapors. Do not eat, drink, or smoke in areas where this material is used.

SECTION 9. Physical and Chemical Properties

Appearance:	N.D.	Physical State:	Liquid
Odor:	Typical	Odor Threshold:	N.D.
Density, g/cm3:	0.842	pH:	N.D.
Freeze Point, °F:	N.D.	Viscosity:	N.D.
Solubility in Water:	Negligible	Explosive Limits, vol%:	0.7 - 5.0
Boiling Range, °F:	492 - 563	Flash Point, °F:	264
Evaporation Rate:	<0.01 (n-butyl acetate=1)	Auto-ignition Temp., °F:	N.D.
Vapor Density:	6 (air=1)	Vapor Pressure:	<0.1 mm Hg at 68°F

(See "Other information" Section for abbreviation legend)

SECTION 10. Stability and Reactivity

STABILITY: No Information

CONDITIONS TO AVOID: Avoid excess heat and sources of ignition.

INCOMPATIBILITY: Prevent contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: During combustion carbon monoxide may be formed. During combustion asphyxiants may be formed. Decomposition releases nitrogen oxides. Decomposition causes sulfur oxides to be released.

HAZARDOUS POLYMERIZATION: No Information

SECTION 11. Toxicological Information



Information on Toxicological Effects

EFFECTS OF OVEREXPOSURE - INHALATION: Vapors can cause irritation of the respiratory tract. High concentrations can cause headache, nausea, weakness, lightheadedness, and stupor (CNS depression). Breathing in the material may irritate the mucous membranes of the nose, throat bronchi and lungs.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). Personnel with pre-existing skin disorders should avoid contact with this product.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful or fatal if liquid is aspirated into lungs. Ingestion may cause

gastrointestinal tract irritation. May cause diarrhea.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: May cause delayed lung damage. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

Primary Route(s) of Entry: Eye Contact, Ingestion, Inhalation, Skin Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	<u>Oral LD50, mg/kg</u>	<u>Dermal LD50, mg/kg</u>	Vapor LC50, mg/L
64742-46-7	Straight run middle distillate	>5,000	>2,000	>20.0

SECTION 12. Ecological Information

ECOLOGICAL INFORMATION: No Information

SECTION 13. Disposal Considerations



For more guidance and information contact our Waste Services Division at (262) 658-4000.

Always dispose of any waste in accordance with all local, state, and federal regulations.

DISPOSAL METHOD: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways. Use only noncombustible material for clean-up. Use clean, non-sparking tools to collect absorbed materials. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. If leak or spill has not ignited, use water spray to disperse the vapors. Do not touch or walk through spilled material. Stay upwind of spill. Ventilate spill area. Collect spilled materials for disposal. Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.)

SECTION 14. Transport Information

DOT Proper Shipping Name:	Not Regulated	Packing Group:	None
DOT Hazard Class:	No Information	Hazard SubClass:	No Information
DOT UN/NA Number:	No Information	Resp. Guide Page:	No Information

SECTION 15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

U.S. State Regulations: NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product are at or greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: No Information

SECTIC	N 16. Othe	er Information					
Revision D	ate:	06/18/2018	3	Supersedes Date:		10/9/2014	
Datasheet	produced by:	EH&S - Re	gulatory Depa	rtment			
HMIS Rati	ngs:						
Health:	1	Flammability:	1	Reactivity:	0	Personal Protection:	Х
Volatile Organic Compounds, gr/ltr: DISCLAIMER: THE VOLATILE ORGANIC COMPOUND (VOC) CONTENT REPORTED HEREIN, IF ANY, IS BASED ON A MATERIAL VOC CALCULATION. NOTE THAT SEVERAL METHODS ARE USED FOR CALCULATING VOC CONTENT AND THAT STANDARDS/ REQUIREMENTS REGARDING VOC CONTENT VARY BY LOCATION/JURISDICTION. ACCORDINGLY, RelaDyne MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, REGARDING THIS MATERIAL'S COMPLIANCE WITH VOC STANDARDS/REQUIREMENTS APPLICABLE IN LOCATIONS/JURISDICTIONS WHERE THIS MATERIAL MAY BE SOLD OR USED.							
Text for G	HS Hazard S	tatements shown		·	ngredient:		

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H320 Causes eye irritation

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this SDS was obtained from sources which we believe to be reliable. However, the information provided is without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the product itself. The information and recommendations are offered for the user's consideration and examination and should be used to make an independent determination of the methods to safeguard workers and the environment. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For these reasons we do not assume responsibility and expressly disclaim any liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this SDS may not be applicable. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.