SAFETY DATA SHEET



1. Identification

Product identifier	RelaTECH Soluble Oil 2560	
	METALWORKING FLUID	
Other means of identification		
Product number	951622560SO	SDS# 399
Recommended use	METALWORKING FLUID	
Recommended restrictions	None known	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name	Reladyne, LLC 8280 Montgomery Road, Suite 101	
Telephone (General Information)	Cincinnati, OH 45236 www.reladyne.com	
Emergency telephone number	INFOTRAC 800-535-5053	

2. Hazard(s) identification

Physical hazards Health hazards	Not classified. Serious eye damage/eye irritation	Category 2 Effects on or via lactation
Environmental hazards OSHA defined hazards Label elements	Reproductive toxicity Not classified. Not classified.	

Signal word	Warning
Hazard statement	Causes serious eye irritation. May cause harm to breast-fed children.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not breathe mist or vapor. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.
Storage	Store in accordance with local/regional/national/international regulation. Store in a well-ventilated area. Keep container tightly closed. Protect from sunlight. Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM		64742-52-5	60 - 100
C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN		63449-39-8	5 - 10
DIETHYLENE GLYCOL		111-46-6	0.5 - 1.5
PETROLEUM SULFONIC ACID, SODIUM SALT		68608-26-4	0.5 - 1.5
2-BUTOXYETHANOL		111-76-2	0.1 - 1
Other components below reportable level	s		7 - 13

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention.
5. Fire-fighting measures	
Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathefumes.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions,
protective equipment and
emergency proceduresKeep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear
appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor.
Ensure adequate ventilation. Local authorities should be advised if significant spillages cannotbe
contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand orearth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe mist or vapor. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. To maintain product quality, do not store in heat or direct sunlight. Store in original tightly closed container. Room temperature - normal conditions. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S OSHA		
	Туре	Value
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	PEL	5 mg/m3
US. OSHA Table Z-1 Limits for Air Cor	ntaminants (29 CFR 1910.1000)	
	Туре	Value
2-BUTOXYETHANOL (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm
U.S NIOSH		
	Туре	Value
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	STEL	10 mg/m3
	TWA	5 mg/m3
US. NIOSH: Pocket Guide to Chemica	l Hazards	
	Туре	Value
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	24 mg/m3
		5 ppm
ACGIH		
	Туре	Value
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	TWA	5 mg/m3

US. ACGIH Threshold Limit Values

	Туре	Value
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	20 ppm
Exposure guidelines		
US - California OELs: Skin	designation	
2-BUTOXYETHANOL (Can be absorbed through the skin.
US - Minnesota Haz Subs:	Skin designation applies	
2-BUTOXYETHANOL (C	,	Skin designation applies.
US - Tennessee OELs: Ski	U	
2-BUTOXYETHANOL (,	Can be absorbed through the skin.
	Chemical Hazards: Skin de	0
2-BUTOXYETHANOL (Can be absorbed through the skin.
	for Air Contaminants (29 C	-
2-BUTOXYETHANOL (C	,	Can be absorbed through the skin.
Appropriate engineering controls	should be matched to cond or other engineering contro exposure limits have not be	typically 10 air changes per hour) should be used. Ventilation rates ditions. If applicable, use process enclosures, local exhaust ventilation, bls to maintain airborne levels below recommended exposure limits. If een established, maintain airborne levels to an acceptable level. Eye ency showers are recommended.
Individual protection measures	s, such as personal protective	veequipment
Eye/face protection	Wear safety glasses with s	side shields (or goggles). Eye wash fountain is recommended.
Skin protection		
Hand protection	Use protective gloves mac	le of: Nitrile.
Other	Wear suitable protective cl	othing and gloves. Use of an impervious apron is recommended.
Respiratory protection	In case of insufficient vention	ilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal	protective clothing, when necessary.
General hygiene considerations	good personal hygiene me	ink or smoke. Do not get in eyes, on skin, on clothing. Always observe asures, such as washing after handling the material and before eating, Routinely wash work clothing and protective equipment to remove

9. Physical and chemical properties

, , ,	
Appearance	AMBER
Physical state	Liquid.
Form	Liquid.
Color	Amber.
Odor	CHEMICAL
Odor threshold	Not available.
рН	Not Applicable
Melting point/freezing point	< 32 °F (< 0 °C)
Initial boiling point and boiling range	> 212 ℉ (> 100 ℃)
Flash point	> 350 °F (> 160 °C) Cleveland Open Cup
Evaporation rate	Like water when diluted
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.

Relative density	Not available.
Solubility(ies)	100 % Water Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
pH in aqueous solution	9.4 @ 5%
Specific gravity	0.98
VOC ASTM D2369	16 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Avoid contact with oxidizers or reducing agents.
Hazardous decomposition products	Smoke, fumes, hydrogen chloride, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May be harmful if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Components	Species	Test Results
2-BUTOXYETHANOL (CAS	S111-76-2)	
Acute		
Dermal		
LD50	Rabbit	400 mg/kg
Inhalation		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
DIETHYLENE GLYCOL (C	AS 111-46-6)	
Acute		
Dermal		
LD50	Rabbit	11890 mg/kg

Components	Species	Test Results
Oral		
LD50	Cat	3300 mg/kg
	Dog	9000 mg/kg
	Guinea pig	8700 mg/kg
	Mouse	13.3 g/kg
	Rabbit	26.9 g/kg
	Rat	12565 mg/kg
SEVERELY-HYDROTREATED N	APHTHENIC PETROLEUM (CAS 64742-52-5)	
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Inhalation		
LC50	Rat	5.7 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
* Estimates for an dust may d		
Skin corrosion/irritation	be based on additional component data not shown. Prolonged skin contact may cause temporary irritati	on Defatting drying and cracking of skin
	Direct contact with eyes may cause temporary irritat	
Serious eye damage/eye rritation	Direct contact with eyes may cause temporary inita	ion.
Respiratory or skin sensitization	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any compor	
	mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation of Carcinogenicity	
2-BUTOXYETHANOL (C		to carcinogenicity to humans.
	ulated Substances (29 CFR 1910.1001-1050)	
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive of	or developmental effects.
Specific target organ toxicity - single exposure	- Not classified.	
Specific target organ toxicity -	y - Not classified.	
epeated exposure		
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information	n	
•		us offects to the environment. Toxic to equatic
Ecotoxicity	Contains a substance which causes risk of hazardous effects to the environment. Toxic to aquation life with long lasting effects.	
Components	Species	Test Results
2-BUTOXYETHANOL (CAS 1	-	
Aquatic	,	
Fish	LC50 Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
C14-C17 MEDIUM CHAIN C	HLORINATED PARAFFIN (CAS 63449-39-8)	-
Aquatic	(
Fish	LC50 Bluegill (Lepomis macrochirus)	> 0.1 mg/l, 96 hours
DIETHYLENE GLYCOL (CAS		
Δαματίς		
Aquatic Fish	LC50 Western mosquitofish (Gambusia af	finis) $> 32000 \text{ mg/} 06 \text{ hours}$

Components		Species	Test Results
SEVERELY-HYDROTREA	ED NAPHTH	HENIC PETROLEUM (CAS	64742-52-5)
Aquatic			
Acute			
Fish	LC50	Fish	> 100 mg/l, 96 hours
* Estimates for product may	be based or	additional component dat	a not shown.
rsistence and degradability		s available on the degrada	
oaccumulative potential		-	
Partition coefficient n-oct 2-BUTOXYETHANOL	anol / water	(log Kow) 0.83	3
obility in soil	No data a	available.	
ther adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
3. Disposal considerati	ons		
isposal instructions	Consult a chemical	Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.	
ocal disposal regulations	Dispose	in accordance with all appl	icable regulations.
azardous waste code		The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
/aste from residues / unused roducts	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
ontaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.		
4. Transport informatio	n		
OT			
UN number	Not Reg	ulated	
UN proper shipping name	-		
Transport hazard class(es	:)		
Class	Not Regi	ilated	
Subsidiary risk	Not neg	liated	
Label(s)			
Packing group			
Environmental hazards			
Special provisions	Not Regi ser Read safe	ulated (See below) ety instructions, SDS and e	emergency procedures before handling.
Packaging exceptions Packaging non bulk			
Packaging bulk			
Supplemental Information:			ges (119 gallons or less) from Marine Pollutant Requirement
unless all or part of the ship	ment is by ve	essel.	
UN number	Not room	lated in small packages	
UN proper shipping name	-	Not regulated in small packages	
Transport hazard class(es	;)		
Class Subsidiary risk			
Packing group			
Environmental hazards			
ERG Code	_		
Special precautions for up	ser Read safe	etv instructions SDS and e	emergency procedures before handling.

Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
IMDG	
UN number	Not regulated (in small containers)
UN proper shipping name	
Transport hazard class(es) Class Subsidiary risk Packing group Environmental hazards Marine pollutant EmS Special precautions for use	r Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

General information

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazar	d cata	aories
nazar	u cale	aories

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water ActNot regulated.(SDWA)Not regulated.Food and DrugNot regulated.Administration (FDA)Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

US. Massachusetts RTK - Substance List

2-BUTOXYETHANOL (CAS 111-76-2)

US. New Jersey Worker and Community Right-to-Know Act

2-BUTOXYETHANOL (CAS 111-76-2)

US. Pennsylvania Worker and Community Right-to-Know Law

2-BUTOXYETHANOL (CAS 111-76-2) DIETHYLENE GLYCOL (CAS 111-46-6)

US. Rhode Island RTK

Not regulated.

California South Coast Air	This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the
Quality Management	SCAQMD. The VOC content of the product is 105 g/L, measured by ASTM Method E-1868-10.
District (SCAQMD) Rule	This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration
1144 (VOC Emissions)	is 71 % to maintain compliance.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico *A "Yes" indicates this product co	Toxic Substances Control Act (TSCA) Inventory mplies with the inventory requirements administered by the governing country	Yes Yes

16. Other information, including date of preparation or last revision

Issue date Revision date	05-27-2016 06-01-2018
Version #	02
Further information	Not available.
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	OSHA Hazard Communication Standard 29 CFR 1910.1200 and GHS