

DuraMAX[®]

ANTIFREEZE AND COOLANT



Formulated to work with All Vehicles. Universally works with all fluid colors; all OAT, POAT, HOAT & IAT.

5-year/150,000-mile Extended Life Formula.

Meets or exceeds ASTM D3306 & D4985 for corrosion protection.

**Protects your car or light duty truck for up to 5 years or 150,000 miles (240,000 km) when flushed and filled according to instructions.

DuraMAX®

CONCENTRATE AMAM EXTENDED LIFE

GENERAL DESCRIPTION

Composition by Weight

Inhibited Glycols:	98.0%
Total Water:	2.0%
Dyes:	Trace

Properties Typical Values Tests

Color:	Yellow	
Odor:	Characteristic	
Ash Content:	1.20%	ASTM D1119
pH: (50% by Vol. Solution)	8.7	ASTM D1287
Reserve Alkalinity:	5.15	ASTM D1121
Specific Gravity at 20/20°C: (50% by Vol. Solution)	1.0687	ASTM D1122
Freezing Point (50% by Vol. Solution):	-34°F	ASTM D1177
Boiling Point**:	+226°F	ASTM D1120
Foam Test:	50 ml max, 1.0 sec. max break time	ASTM D1881

**Under standard pressure

PROTECTION	FREEZE-UP PROTECTION	BOIL-OVER PROTECTION†	CORROSION PROTECTION
MINIMUM 50% Antifreeze 50% Water	-34°F	+265°F	Meets or exceeds ASTM D3306 ASTM D4985
MAXIMUM 70% Antifreeze 30% Water	-84°F	+276°F	

† Using a 15 lb. pressure cap in good condition

DuraMAX® All Makes All Models

**CONCENTRATE ALL MAKES ALL MODELS
EXTENDED LIFE
UP TO 150,000 MILES / 5 YEARS***

PRODUCT	950820100AM0807
ITEM UPC	0 53252-26421 8
DRUM	950820100AM0810
BULK	950820100AM0812
CASE UPC	0 53252-26426 3

50/50 PREDILUTED AMAM EXTENDED LIFE

GENERAL DESCRIPTION

Composition by Weight

Antifreeze/Coolant Concentrate:	51.0%
Total Water:	49.0%
Dyes:	Trace

Properties Typical Values Tests

Color:	Yellow	
Odor:	Characteristic	
Ash Content:	0.58%	ASTM D1119
pH:	8.7	ASTM D1287
Reserve Alkalinity:	2.6	ASTM D1121
Specific Gravity at 20/20°C:	1.0687	ASTM D1122
Freezing Point:	-34°F	ASTM D1177
Boiling Point**:	+226°F	ASTM D1120
Foam Test:	50 ml max, 1.0 sec. max break time	ASTM D1881

**Under standard pressure

PROTECTION	FREEZE-UP PROTECTION	BOIL-OVER PROTECTION†	CORROSION PROTECTION
50/50 PREDILUTED Antifreeze/Coolant	-34°F	+265°F	Meets or exceeds ASTM D3306 ASTM D4985

† Using a 15 lb. pressure cap in good condition

DuraMAX® All Makes All Models

**50/50 PREDILUTED
ALL MAKES ALL MODELS EXTENDED LIFE
UP TO 150,000 MILES / 5 YEARS***

PRODUCT	950825050AM0807
ITEM UPC	0 53252-26405 8
DRUM	950825050AM0810
BULK	950825050AM0812
CASE UPC	0 53252-26456 0

Case Pack:	Case Size (in.):	Case Weight (lb.):	Case Cube (cu ft.):	Pallet Load Size (in.):	Cases Per Tier:	Tiers Per Pallet:	Cases Per Pallet:	Load Weight (lb.):
6	L 15.75 x W 12.94 x H 12.19	60	1.437721615	L 47.25 x W 38.81 x H 48.75	9	4	36	2150

* Provides extended life protection for up to 5 years/150,000 miles when flushed and filled according to manufacturer's recommendations.